

---

## EXTERIOR POWDER FILLER

### CEMENT BASED FILLER

---

#### DESCRIPTION

Bostik Exterior Powder Filler is a cement-based filler, reinforced by acrylic to reduce shrinking and cracking and aid water resistance for exterior use. When dry (5-6 hours) it can be nailed or screwed without cracking or splitting. Sand lightly to provide an excellent base for painting. It can also be used as a filler in interior wet areas.

---

#### FEATURES AND BENEFITS

- All purpose interior and exterior-grade filler.
- Ideal for filling cracks and holes in brick, wood, cement sheet, plaster, stone and masonry.
- Weather and water resistant.
- Can be nailed or screwed without cracking.

---

#### PRECAUTION

Adding water once mixed will not increase working time. After use, filler should not be exposed to water for 24 hours to ensure maximum hardening. If movement occurs, use Bostik Fill-a-Gap.

---

#### PROPERTIES

Type:	Acrylic-reinforced cement
Colour:	Grey
Shelf life:	5 years, if kept airtight in original container

---

#### SURFACE PREPARATION

Surfaces should be clean and dry with no loose or powdery material or paint. Do not wet or prime surface before applying. Coat nail-heads with oil-based primer to stop rust staining of filler or final painted surface.

---

#### APPLICATION

- Mix up enough paste for requirements in a clean container. Paste has at least 1 hour's working time.

---

**Wellington Site (Factory & Admin)**  
**Auckland Site**

**19 Eastern Hutt Road, Wingate, Lower Hutt**  
**148 Pavilion Drive, Airpark II, Auckland Airport**

Ph ++64 4 567 5119      Fax ++64 4 567 5412  
Ph ++64 9 257 5847      Fax ++64 9 257 3588

**[www.bostik.co.nz](http://www.bostik.co.nz)**

This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit [www.bostik.co.nz](http://www.bostik.co.nz)

- Mix approximately 4 parts powder to 1 part water; this should be toothpaste consistency. For deeper filling applications, a slightly stiffer consistency will aid filling ability, and also reduce drying time.
  - Using a flexible-filling blade, apply a thick coat to the area to be filled or patched.
  - Scrape off excess.
  - Allow 5-6 hours to dry before sanding.
  - When dry, sand lightly (120-grit sandpaper) for an excellent surface for painting.
  - Using a primer will further enhance weather ability of this product. Match topcoat to primer / undercoat using either an oil-based or water-based system.
  - Bostik Exterior Powder Filler can be painted with water or oil based paints.
- 

### PACKAGING

Available in 500gm, 2kg, and 5kg containers

---

### STORAGE

Close lid tightly after use. Reseal any opened bags. Keep in original container. Store in a cool, dry place out of direct sunlight.

---

### CLEANING

Clean tools and hands with soapy water.

---

### HEALTH & SAFETY

A Material Safety Data Sheet is available on request. Bostik Exterior Powder Filler is non-toxic and non-hazardous. However, due to irritation of dust, wear safety glasses and a dust mask when mixing up paste and when sanding.

---

### VERSION

V1                      5 March 2012      New issue