



Technical Data Sheet

05/08/2011



Quality
ISO 9001

BOSTIK FILL-N-FIX

DESCRIPTION

Bostik Fill-N-Fix is a multi-purpose ready mixed high quality compound for filling gaps and cracks in timber, concrete, plaster, stone and metal. Fill-N-Fix may be used as an interior or exterior finish with excellent water resistance. Shrinkage has been reduced to virtually nil by using space age fillers, no overfilling required. Odour while wet is minimal which makes it ideal for interior uses.

SPECIFICATION

Type:	Acrylic resins plus special fillers.
Colour:	White
Density:	Approx 1.3
Solid content:	Approx 75 %
Sandability:	Excellent
Flexibility:	Limited, use Bostik Fillagap for moving joints.
Solvent:	Water when wet, turps when dry.
Odour :	Wet - virtually nil ; dry - none
Trowellability:	Excellent / soft paste
Slump:	Nil

Wellington Site (Factory & Admin)
Auckland Site

19 Eastern Hutt Road, Wingate, Lower Hutt
148 Pavilion Drive, Airpark II, Auckland Airport

Ph ++64 4 567 5119
Ph ++64 9 257 5847

Fax ++64 4 567 5412
Fax ++64 9 257 3588

www.bostik.co.nz

This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.co.nz

APPLICATION

- All surfaces must be clean, dry and free from dust or grease. Prepare most surfaces by sanding and wiping dry.
- Using a putty knife or spatula press Bostik Fill-N-Fix into the joint or hole. Each layer may be up to about 6 mm thick. Allow to dry between layers if over 6 mm.
- Allow to dry 12 hours for thin and 24 hours for thick layers.
- Sand smooth and paint with water or solvent based paint, following the manufacturer's recommendations for exterior work.
- Do not use Bostik Fill-N-Fix in conditions where it will be continuously wet. Painted and fully dried Fill-N-Fix is suitable for exterior timber.

STORAGE

Store in cool, dry conditions out of direct sunlight between 5°C and 25°C. This product **MUST** be protected from frost.

PACKAGING

500 gram, 250 gram

SHELF LIFE

12 months stored at room temperature in original unopened containers.

VERSION

Version 4

5th August 2011