



Technical Data Sheet

6 March 2012



Quality
ISO 9001

INTERIOR POWDER FILLER

DESCRIPTION

Bostik Interior Powder Filler is a plaster-based filler, reinforced by cellulose to reduce shrinking and cracking. When dry (2-3 hours for small holes or 5-6 hours for larger areas) it can be nailed or screwed without cracking or splitting. Sand lightly for an excellent base for painting

RECOMMENDED USES

- Ideal for filling holes and cracks in brick, wood, plasterboard, plaster and masonry
 - All purpose interior-grade plaster filler
-

FEATURES AND BENEFITS

Can be nailed or screwed without cracking

APPLICATION

PREPERATION

Surfaces should be clean and dry with no loose or powdery material or paint. Mixing containers must be clean with no filler residue otherwise drying time will be significantly shortened.

APPLICATION

- Do not wet or prime surface before applying.
 - Mix up enough paste for requirements. Using a mechanical beater will reduce pot life. The plaster has a 45-60 minute working time when mixed according to instructions, depending on atmospheric conditions.
 - Working time will be shortened at higher temperatures.
 - Mix 2.5 parts powder to 1 part water in a clean container, this should be toothpaste consistency. For deeper filling applications, a slightly stiffer consistency will aid workability and reduce drying time.
 - Scrape a small amount of filler onto a flexible filling blade.
 - Apply thin layers pressing firmly into the area being filled. Allow each layer to dry before applying next layer.
 - Remove any excess filler.
 - Dries in 2-3 hours in thin applications or 5-6 hours in larger areas depending on atmospheric conditions.
 - When dry, sand lightly (120-240 grit sandpaper) for an excellent surface for painting.
 - For optimum results, allow 12-24 hours for product to harden fully prior to sealing the surface.
-

Wellington Site (Factory & Admin)
Auckland Site

19 Eastern Hutt Road, Wingate, Lower Hutt
148 Pavilion Drive, Airpark II, Auckland Airport

Ph ++64 4 567 5119
Ph ++64 9 257 5847

Fax ++64 4 567 5412
Fax ++64 9 257 3588

www.bostik.co.nz

This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.co.nz

- Seal Bostik Interior Powder Filler with an appropriate primer or undercoat prior to applying top coat.
-

PRECAUTIONS

- Adding water once mixed will not increase working time.
 - Not suitable for outdoor use, or filling large holes – use
 - Bostik Exterior Powder Filler instead. If movement occurs, use Bostik Fill-a-Gap.
-

PACKAGING

Available in 500gm, 1kg, 2kg, 5kg and 10kg containers

PROPERTIES

Type: Cellulose-reinforced plaster powder
Colour: White

PAINTABILITY

Bostik Interior Powder Filler can be painted with water or oil based paints

STORAGE

- Close lid tightly after use
 - Reseal any opened bags. Keep in original container.
 - Store in a cool, dry place out of direct sunlight
-

CLEANING

Clean tools and hands with soapy water.

HEALTH AND SAFETY

Bostik Interior Powder Filler is non-toxic. As with all plaster-based powder, over prolonged exposure, small amounts of silica present are regarded as cancer-causing in the lungs if inhaled. Therefore, avoid breathing in powder when mixing and dust when sanding by wearing a full dust mask.

Full details are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that the appropriate Safety Data Sheets are read by all concerned. Visit www.bostik.co.nz for copies.

VERSION

V1 6 March 2012 New format