



## Technical Data Sheet

Date: 8 February 2012



Quality  
ISO 9001

---

# KWIKSET

## LIGHT WEIGHT FILLER

---

### DESCRIPTION

Bostik KwikSet light weight filler is a ready to use repair paste, suitable for filling interior cracks, chips and holes in plaster, plasterboard, wallboard and wood.

---

### RECOMMENDED USES

- Use on mortar, concrete, timber, plaster, and primed metal.
- Suitable for repairs to plaster and plasterboard.

---

### FEATURES AND BENEFITS

- Paintable in 30 minutes
- Ready to use
- Applicator included

---

### APPLICATION

- Surfaces should be clean and dry with no loose or powdery material or paint.
- Prime any exposed nail heads prior to use
- Using applicator provided, apply KwikSet to required area pressing firmly into hole/crack.
- Smooth off area and allow to dry for 30 minutes in thin areas, allow a longer time period for deeper holes/cracks and on non – porous surfaces
- KwikSet can be sanded and painted when dry (allow 24 hours drying time before using an oil based paint).

---

### CLEANING

Clean tools and hands with soapy water while still wet.

---

### PRECAUTION

- Not suitable for outdoor use
- Use flexible filler where joint movement occurs

---

**Wellington Site (Factory & Admin)**  
**Auckland Site**

**19 Eastern Hutt Road, Wingate, Lower Hutt**  
**148 Pavilion Drive, Airpark II, Auckland Airport**

Ph ++64 4 567 5119      Fax ++64 4 567 5412  
Ph ++64 9 257 5847      Fax ++64 9 257 3588

**[www.bostik.co.nz](http://www.bostik.co.nz)**

This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit [www.bostik.co.nz](http://www.bostik.co.nz)

---

**PACKAGING**

Available in 350ml and 750ml container with applicator.

---

**PROPERTIES**

Typical properties after 7 days cure at 25°C and 50% RH

Appearance	Ready to use paste
Chemical Type	Water based acrylic
Colour	White
Density	Approximately 0.5

---

**STORAGE**

- 12 months in unopened container when stored in a cool place out of direct sunlight
  - Close lid tightly after use.
  - If product appears to dry stir in 1 teaspoon of water with applicator.
- 

**HEALTH AND SAFETY**

Bostik KwikSet is non-toxic and non-hazardous

Full details are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that the appropriate Safety Data Sheets are read by all concerned. Visit [www.bostik.co.nz](http://www.bostik.co.nz) for copies.

---

**VERSION**

V1      8 February 2012      Localisation