



Technical Data Sheet

Date: 8 February 2012



LINSEED OIL PUTTY

DESCRIPTION

Bostik Linseed Oil Putty is a linseed oil-based putty for filling wood surfaces prior to painting. It can be used inside or out for a professional finish. It can also be used for bedding windows into frames.

FEATURES & BENEFITS

- High-grade linseed oil based putty
- Ideal for timber window frames and door panels
- Weather and water resistant
- Can be nailed or screwed without cracking

PROPERTIES

Typical properties after 7 days cure at 25°C and 50% RH

Type	Linseed oil putty
Colour	Beige
Shelf Life	12 months

APPLICATION

PREPARATION

Surfaces should be clean and dry with no loose or powdery material or paint.

APPLICATION INSTRUCTIONS

- Prime bare timber with an oil-based primer and allow to dry before applying Bostik Linseed Oil Putty. This will prevent excessive shrinkage or poor adhesion of putty.
- Knead putty before applying.
- Apply putty with a putty knife, pushing putty firmly into hole or crack to be filled. Smooth the surface with flat blade of knife.
- Allow 2 days up to 1 month for putty to skin depending on atmospheric conditions. Linseed oil putty may remain soft to touch for some months after application.
- The setting time of putty may vary significantly depending on the weather, environmental conditions, exposure to direct sunlight, and if used on timber windows, whether previously primed or otherwise treated as recommended.
- Paint over putty only when sufficiently set. If left too long before painting, putty will harden excessively and crack, if painted too early, the excess oil in the putty will lift the paint and cause slating and wrinkle the surface layer.
- Apply oil-based undercoat before painting.

Wellington Site (Factory & Admin)
Auckland Site

19 Eastern Hutt Road, Wingate, Lower Hutt
148 Pavilion Drive, Airpark II, Auckland Airport

Ph ++64 4 567 5119
Ph ++64 9 257 5847

Fax ++64 4 567 5412
Fax ++64 9 257 3588

www.bostik.co.nz

This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Sale of the product by Bostik is subject to the Bostik New Zealand Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.co.nz

- Replace paper disc on putty and tightly close lid when finished.
-

CLEANING

Clean tools and hands with soapy water.

PACKAGING

Available in 400gm and 1.75kg containers.

STORAGE

Replace paper disc on putty and tightly close lid when finished. Store in a cool place out of direct sunlight.

PRECAUTION

Whilst Bostik Linseed Putty remains flexible, Bostik Fill-a -Gap or Bostik Seal-n-Flex should be used where significant movement occurs. In strong sunlight some shrinkage may occur, appropriate priming and painting will reduce this.

HEALTH & SAFETY

Avoid prolonged contact with skin.

Full details are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that the appropriate Safety Data Sheets are read by all concerned. Visit www.bostik.co.nz for copies.

VERSION

V1 8 February 2012 Localisation