

1 IDENTIFICATION OF THE PRODUCT AND OF THE SUPPLIER

Product Name PLUMBERS PUTTY

Hazard Statement Classified as Not Hazardous according to HSNO in New Zealand.

Not classified as a Dangerous Good according to NZS5433:1999

Transport of Dangerous Goods on Land.

Recommended Use Non-drying, water resistant putty which adheres to a wide range of solid

surfaces.

Supplier Bostik New Zealand Limited

Street Address 19 Eastern Hutt Road, Wingate, Lower Hutt, New Zealand

 Telephone
 ++64 4 567 5119

 Facsimile
 ++64 4 567 5412

 Website
 www.bostik.co.nz

Emergency Telephone Number National Poisons Centre

0800 POISON or 0800 764 766

Emergency Response In New Zealand 0800 CHEMCALL or 0800 243 622

In Australia 1800 127 406
Globally ++64 3 353 0199

Date of Preparation 01 April 2006

2 HAZARDS IDENTIFICATION

Hazard StatementNot hazardousPrecautionsNot applicableHSNO ClassificationsNot applicable

3 COMPOSITION / INFORMATION ON INGREDIENTS

Chemical NameCASProportionNon-hazardous ingredients-100%

Plumbers Putty Substance Number: 164620



4 FIRST AID MEASURES

If poisoning occurs, contact the National Poison Centre (New Zealand 0800 POISON or 0800 764 766).

First Aid

Inhalation Unlikely to be a route of exposure. However, if inhalation is suspected,

remove person to fresh air. Get medical advice if breathing becomes

difficult.

Skin Contact Remove contaminated clothing and wash skin with warm soapy water.

Do not scrub. If swelling, redness, blistering or irritation occurs, get

medical assistance.

Eye Contact Hold open and flood with water for at least 15 minutes. Get medical

advice.

Ingestion Rinse mouth with water. Do not induce vomiting, give a glass of water to

dilute and get medical advice immediately. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water.

Advice to Physician Treat symptomatically.

5 FIRE FIGHTING MEASURES

Type of Hazard Non-flammable material.

HAZCHEM Code Not applicable

Fire Hazard Properties Not applicable

Extinguishing Media Not flammable, however if material is involved in a fire use water fog (or

if unavailable a fine water spray), foam, or dry agent (carbon dioxide, dry

chemical powder).

Unsuitable

Extinguishing Media

Not applicable

Precautions for Firefighters

Not applicable

Additional Advice Not applicable

Plumbers Putty Substance Number: 164620

Issued: <u>02/02/2012</u> Version: <u>2</u> Page 2 of 6



6 ACCIDENTAL RELEASE MEASURES

Spills Sweep up and dispose of as per Section 13 of this SDS.

7 HANDLING AND STORAGE

Handling No special precautions are required when handling this product at normal

application temperatures.

Storage Store in a cool, dry place and out of direct sunlight. Store away from any

incompatible materials as defined in Section 10 of this SDS. Keep containers

closed when not in use.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace Exposure Guidelines

Substance WES-TWA WES-STEL

Not applicable -

Engineering Controls Natural ventilation should be adequate under normal conditions of use.

Personal Protection

Equipment

None required.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance Thick white putty

Odour No odour

Boiling Point °C Not applicable

Specific Gravity 1.7

Solubility in Water Very low

High = >60% Medium = 10% - 60% Low = 1% - 10% Very Low = < 1%

10 STABILITY AND REACTIVITY

Stability of Substance This material is thermally stable when stored and used as directed.

Plumbers Putty Substance Number: 164620

Issued: 02/02/2012 Version: 2 Page 3 of 6



Conditions to AvoidNo information available.

Incompatible Materials No information available.

Hazardous Decomposition

Products

Thermal decomposition is highly dependant on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or

oxidative degradation.

Hazardous Reactions No information available.

11 TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation Product may be an irritant to mucous membranes and respiratory

tract if used at elevated temperatures.

Skin Contact Contact with skin may result in irritation. Repeated or prolonged

contact may lead to irritation.

Eye Contact May be an eye irritant.

Ingestion Swallowing could result in nausea and vomiting.

Long Term Effects No information available.

12 ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Ecotoxicity Not classified as Ecotoxic under HSNO.

Persistence and degradability The product is expected to biodegrade slowly.

Mobility Not soluble in water.

13 DISPOSAL CONSIDERATIONS

Substance Disposal Dispose of in an authorised landfill. Do not dispose of down drains

or into local waterways.

Plumbers Putty Substance Number: 164620

Issued: 02/02/2012 Version: 2 Page 4 of 6



Container Disposal Recycle or reuse if possible, or dispose of in an authorised landfill.

Local Legislation Disposal should be in accordance with applicable regional and

national laws and regulations.

14 TRANSPORT INFORMATION

Land Transport

Not classified as Dangerous Goods by the criteria of NZS 5433:1999 Transport of Dangerous Goods on Land for transport by road or rail.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15 REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Environmental Risk Management Authority (ERMA) Group Standard Number:

Not applicable.

Hazardous Substances and New Organisms Act (HSNO):

Approved Handler not required.

16 OTHER INFORMATION

SDS Revisions Safety Data Sheets are updated at least every 5 years. Obtain the latest

version by visiting www.bostik.co.nz.

A vertical bar in the margin indicates an amendment from the previous

version.

Reason for Issue SDS review

SDS Distribution The information in this document should be made available to all who may

handle this product.

Plumbers Putty Substance Number: 164620

Issued: <u>02/02/2012</u> Version: <u>2</u> Page 5 of 6



This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of this product, and in particular how to safely handle and use the product in the workplace. Since Bostik New Zealand Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact Bostik New Zealand Limited.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is available upon request.

Key / Legend

,-	
SDS	Safety Data Sheet
HSNO	Hazardous Substances and New Organisms Act 1996
WES-TWA	The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure.
WES-STEL	The 15 minute average exposure standard. This applies to any 15 minute period in a working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to WES-TWA; both the short-term and time-weighted average exposures apply.

Disclaimer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Plumbers Putty Substance Number: 164620