

VARIABLE SPEED CONTROL PUMP

MPEP-9000

Automatic horizontal pressure booster pump set
Domestic / Commercial water pump

APPLICATION

Large Home, Motel, sprinkler system, boosting from the top of an apartment. Clean ambient temperature water w/o any solids / debris / sand / silt.

DESIGN FEATURES


- Energy saving
- Soft Start / Stop
- In-built run dry protection
- Automatic recovery after power failure
- Two year parts and labour warranty
- Very low maintenance
- Suitable for use with above (preferred) or below ground water tanks
- Provides constant pressure at variable flow range



TECHNICAL DATA

Construction Casing/impeller	S/Steel / S/Steel	Power Supply Req	230v/1ph/20amps
Operation	VSD (variable speed drive)	Inlet (mm)	32
Pump Type	Multistage	Outlet (mm)	32
Pressure Tank Options	Small Tank (supplied)	Maximum Flow	160 l/min
Motor (kW) P1 / P2	3.2 / 2.4	Maximum Head	84m
Full Load Current (P1/P2)	16 / 9.7 amps	Weight (Kg)	32
Dimensions (mm)	(Height) 450	(Width) 230	(Length) 550

Pump Performance



NOTE: The above Performance graph is measured at pump outlet and based on factory test conditions. Actual performance onsite may differ due to piping and fixture sizing and layout

FOR FURTHER TECHNICAL SUPPORT PLEASE CONTACT WALLACE PUMPS AKLD 09 622 9100 CHCH 03 365 6453 WGTN 04 567 8125 OR VISIT www.dlmwallace.co.nz