TANK REPLACEMENT VALVES.



THE LATEST TECHNOLOGY **AND THE BEST PERFORMANCE**

Since 1957 fluidmaster has manufactured products with a tradition of quality and innovation. Fluidmaster products are engineered specifically to work together for optimised performance and long life.



Auckland Ph: 09 415 6151 Christchurch Ph: 03 341 1048 www.hydroflow.co.nz



Side Entry - Inlet

Features

- Simple to install without special tools
- Fits most side inlet toilet cisterns (6-13 litre)
- New design provides a 40% quieter fill
- Unique quick release coupling nut, for easy access & maintenance
- Works well with high or low water pressure, fast refill
- Easy-to-access screen filter ensures years of troublefree operation
- Water level adjustment for most efficient flush volume
- Anti-siphon/backflow design prevents contamination of fresh water supply
- Corrosion resistant plastic and stainless steel components
- Narrow profile allows a proper fit in slimline WC cisterns
- Absence of lever arm prevents storage tank wall distortion - making support structures unnecessary

Top Entry - Inlet Valve

Code Shank Type Shank Size
747UK Plastic 1/2"
747UKL DZR Brass 1/2"
747EL DZR Brass 3/8"




Bottom Entry - Inlet Valve - (400UKL Shown)

Features

- Simple to install without special tools
- Compact, efficient design fits today's 6-13 litre cisterns
- Works well with high or low water pressure no need to change seals
- Fast refill, with an absolute shut-off after every flush
- Lasts longer by working with water pressure, not against it
- Seals are easy to access; simple to change or replace
- Durable materials stand up to millions of flushes
- Narrow profile allows a proper fit in slimline WC cisterns
- Water supply enters cistern from below water level eliminating
 noise of cascading water

Anti-siphon/backflow design prevents contamination of fresh water supply

Easily adjustable height from 230mm to 355mm provides a universal fit.



Fluidmaste

FLOAT

Bottom Entry - Inlet Valve

Code Shank Type Shank Size 400UK Plastic 1/2"

400UKL DZR Brass 1/2" 400EP Plastic 3/8"

400EL DZR Brass 3/8"

DZR Brass shank prevents crossthreading and stripping (400UKL & 400 EL models)



Auckland Ph: 09 415 6151 Christchurch Ph: 03 341 1048 www.hydroflow.co.nz

Dual Flush - Outlet Valve

Features

- Suits most toilet cisterns with top centre buttons
- Easy to fit and adjust
- Adjustable rod lengths
- Adjustable height, 28mm overflow tube
- Made from Anti Corrosive materials
- Half & full flush paddles
- Half and Full Flush adjustment
- Includes standard chrome 38mm dual flush buttons(other button options available)
- Long lasting silicon seal



Accessories/Spare Parts

Access Panel

- Conceals household plumbing, wiring cables.
- Easy to install, no framing required
- Works in walls and ceilings upto to 20mm thick.
- Snaps in and out of position with no visible clamps or screws
- Can be painted or wallpapered



Standard seal



Low pressure seal



Top Assembly

Auckland Ph: 09 415 6151 Christchurch Ph: 03 341 1048 www.hydroflow.co.nz

