

## IN-GROUND 1500 W-750SK

Domestic/Commercial in ground packaged pump station

### APPLICATION

The Wallace In-Ground 1500 is specifically designed for domestic applications where a dwelling is below the conventional council sewer line and 24 hour storage requirement is necessary.

### DESIGN FEATURES

- New Zealand designed & manufactured polyethylene chamber
- Suitable for all types of ground conditions
- Certified to AS/NZS 4766 polyethylene storage tanks for wastewater and chemicals
- Certified to AS/NZS 1546.1 on site domestic wastewater treatment facilities
- The geometric shape allows for maximum strength under compression while also offering the Advantage of anti-floatation for wet areas
- An electrical junction box is installed on the top of the tank where the power cable for the pump and the high level alarm float switch are terminated
- **Refer to Submersible section for pump technical details (W-750 SK)**



### TECHNICAL DATA

Tank Volume (Litres)	1550	Weight (Pump)	26Kg
Dimensions (mm)	2150 x 1420	Max Head (m)	8 Including Sump Depth
Inspect Hatch (mm)	290 Ø	Alarm (Type)	Audio/Visual Float Activated
Total Weight (Kg)	180	Inlet	100mm PVC class D
Pump (Type)	W-750SK	Discharge	50mm PVC class D
Motor Rating	.75kW, 230v, 7 amps	Valves	50mm non return & isolating

Pump Performance

