

MULTISAN

Fully automatic sewage and waste water pump

APPLICATION

Multisan is suitable for pumping waste water from toilets, bidets, showers and basins from rooms which are below the sewer level, or conditions where small dimensioned discharge pipes are required.

DESIGN FEATURES

- Completely self contained
- Quiet, powerful and fully automatic
- Dry mounted motor and pump
- · Easily installed and serviced
- Designed and built in New Zealand for New Zealand conditions
- 2 year warranty
- High head and flow
- · Can be remotely installed
- Marine models also available
- Choice of pan entry position
- Able to pump to a 8m head with a High Head Impeller (optional)
- Audible alarm featuring phase interruption switching off auto discharging machines (optional)
- Solenoid valve to isolate water supply to plumbing fixtures draining to the pump (optional)
- Carbon filter for internal venting (Check with your local Authority for compliance) (optional)

TECHNICAL DATA

Motor Power (kW)	0.9	Total Tank Volume	17 litres
Temp Continuous / Max	40 / 60°C	Delivery connection	32mm Female
Voltage 50Hz (V)	230 - 240	Delivery Pipe	25mm or 32mm PVC
Cable (m)	1.5	32mm swing check	Supplied
Nominal Current (A)	5	32mm Isolating valve	Supplied
Weight (kg)	11.3	Overall dimensions	515(L) x 295(H) x 200(W)

Pump Performance





