

## SANISTAR 205 W

Compact twin pump sewage disposal unit with Integrated swing check valve

### APPLICATION

Sanistar is suitable for pumping sewage and waste water from toilets, hand basins, showers and from rooms which are below the sewer level. Even if there is natural fall if the sewer is flooded Sanistar will prevent a back up and flooding of the room. Applications include basement rooms or car parks, sanitary facilities in restaurants, hotels, shopping centres, schools and hospitals.

### DESIGN FEATURES

- Flood protected pump station
- Odour and gas tight plastic collecting tank
- Flexible union with integrated soft ball check valve
- Non clogging impeller
- Fully submersible, pressure tight electric motors
- Thermal sensors embedded within windings
- Large diameter stainless steel rotor shaft, pre-lubricated bearings
- Combination of mechanical seal (silicon carbide) and lip seal in oil chamber
- Electronic control box for controlling and monitoring all important functions and advising any problems



### TECHNICAL DATA

Motor Input (kW)	1.6	Tank Inlets (mm)	100 (x3), 150 (x2), 40 (1)
Motor Output (kW)	1.1	Total Volume	95 litres
Voltage 50Hz (V)	230-240 / 1 phase	Operating Volume	45 litres
Speed (rpm)	2900	Discharge Flange	80mm
Nominal Current (A)	7.0	Air Vent Size	70mm
Weight (kg)	92	Max Head Height	10m
Dimensions	Length 750mm	Width 750mm	Height 515mm

Pump Performance

